

Features/Benefits of the Vantage® II

Setting the Standard in Unitary Infrared Heating

Feature	Benefit
Layout & Installation:	
<ul style="list-style-type: none"> ▪ Design based on over 30 years of infrared heating experience ▪ Broad range of high BTUH input burners and tube lengths; straight, "U" or "L" configurations available ▪ Reflectors can be tilted or side reflectors can be added ▪ Designed to readily accept low voltage thermostats ▪ Quick assembly stainless steel couplings ▪ Standard flue connector ▪ Option of decorative grille for drop ceiling applications 	<ul style="list-style-type: none"> ▪ Field-proven product performance ▪ Fits any building size or floor plan ▪ Concentrates heat where needed ▪ Reduces installation cost – no additional transformer required for single heater installation. ▪ Minimizes installation time ▪ Easy vent installation ▪ Aesthetically-appealing look in high visibility areas
Operation:	
<ul style="list-style-type: none"> ▪ Operates with natural gas or LP gas (propane) ▪ Honeywell® SmartValve® II control ▪ Hot surface electronic ignition control ▪ Prepurge and timed trial for ignition with multiple ignition trial ▪ Auto reset from lockout ▪ Low-intensity infrared heat ▪ Deep-dish, high efficiency aluminum reflectors with end caps 	<ul style="list-style-type: none"> ▪ Fuel efficient and environmentally friendly ▪ Combines the gas valve and electronic ignition control functions into one single unit ▪ Reliable start-up ▪ Reduces nuisance lockouts ▪ Resets the system after one hour of lockout and begins another sequence for ignition ▪ Warms people and objects directly, not the air ▪ Maximizes energy reflection; minimizes heat loss by convection
Safety:	
<ul style="list-style-type: none"> ▪ SmartValve® II control provides all gas ignition safety functions ▪ CSA design certified ▪ Electrical and burner components separated by a partition ▪ Stainless steel flex gas connector included ▪ Door interlock switch ▪ Detailed Installation, Operation and Service manual 	<ul style="list-style-type: none"> ▪ Controls gas flow, ignition source and combustion air blower and monitors pressure switch ▪ Independent testing to industry standards ▪ Minimizes negative effects of contaminants and back draft ▪ Reliable, durable gas piping ▪ Halts burner operation for service ▪ Reduces installation time and errors; easier to troubleshoot and repair
Maintenance:	
<ul style="list-style-type: none"> ▪ Diagnostic capability incorporated in burner design ▪ Separate burner compartment ▪ Durable, spot welded burner construction with electrostatically applied paint ▪ Removable burner doors ▪ Mica flame observation window ▪ Three-year limited warranty on all components 	<ul style="list-style-type: none"> ▪ Reduces service time ▪ Protects valuable electrical controls from heat exposure and extends life of componentry ▪ Strong, long-lasting unit ▪ Easy access for service ▪ Flame verification and burner operation easy to observe ▪ No hidden short-term exceptions for electrical and gas components



Roberts-Gordon, LLC
 1250 William Street
 P.O. Box 44
 Buffalo, New York 14240-0044
 Telephone: 716.852.4400
 Fax: 716.852.0854
 Toll Free: 800.828.7450
www.rg-inc.com

Quality in Any Language™